



21D64-2

HOTROD™ SERIES UNIVERSAL NITRIDE IGNITOR UPGRADES

120V nitride upgrade kits for conversion of silicon carbide (flat or spiral).

FEATURES

- HotRod™ replaces over 170 ignitors, HotRod EX™ replaces over 260 ignitor models
- Robust nitride ignitor design for longer life and fewer callbacks - 5 year warranty
- Nitride ignitors with 14.5" and 15.5" leads-stripped ends
- Universal and standard mounting brackets and 2 ceramic wire nuts
- Replaces most silicon carbide ignitors including many Carborundum™ models

SPECIFICATIONS

Operating Voltage.....	102-132 VAC, 60 Hz
Max. Load Current.....	3.0 A @ 132 VAC, 25°C
Warm-Up Time.....	21D64-2: 17 sec. minimum
.....	21D64-44: 8 sec. minimum
Temperature Rating Lead Insulation.....	250°C

HOTROD UNIVERSAL IGNITORS

DESCRIPTION	LEAD LENGTH	MODEL NUMBER	ITEM NUMBER
HotRod Kit includes 120V nitride ignitor, 2 brackets (one universal), 15.5" leads-stripped ends, ceramic wire nuts and mounting screw	15.5"	21D64-2	21D64 002
HotRod 5-pack contains 5 single pack ignitor kits	15.5"	21D64-5PK	21D64-5PK
HotRod EX Kit includes 120V nitride ignitor, 2 brackets (one universal), 14.5" leads-stripped ends, ceramic wire nuts and mounting screw	14.5"	21D64-44	21D64-44

